


THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.

REV.	ECN NO.	DATE	SIGN	DESCRIPTION
A		2020/01/20	Vicky	Initial Released



Pin Out	3 2 1	White Green Black	白 綠 黑
	Pin #	Wire	
C2		3P	
C1		3P	

Pin Assignments Front View

AB-BD XX HL-BDBL-QE XXX

03: 3Pin

XXX: 0.5~99Meters
 A05: 0.5 Meter
 001: 01 Meter
 002: 02 Meters
 :
 099: 99 Meters

- Note:
- * \varnothing Important Dimension
 - * Waterproof Rate: IP68, Mated
IP68: 1M depth of water in 24hours
 - * Connector: Thermoplastic, Black
 - * Pin: Copper Alloy, Gold Plated
 - * Cable: SJTW, 18#*3C, PVC Jacket, Black, OD8.0mm
 - * Cable Length Tolerance: 0.5M: +60/-0mm
 01M: +60/-0mm
 02~03M: +120/-0mm
 04~05M: +160/-0mm
 06~10M: ±100mm
 11~20M: ±200mm
 21~30M: ±300mm
 31~99M: ±500mm

UNIT:mm		TITLE	ACC, XLOK, B-5A, DB-ENDED MF		ITEM NO	DRAWN BY	DATE
TOLERANCE	±0.5mm	SCALE	1:2	SIZE A4	DWG NO	CHECKED BY	DATE
		REV.	A	WC-REV. A.5	AB-BDXXHL-BDBL-QEXXX	APPROVED BY	DATE
				\varnothing : Inspection item	CUSTOMER		DATE
					ALTW	Max	2020-01-20
						Vicky	2020-01-20
						Rita	2020-01-20

Amphenol LTW
 安費諾亮泰企業股份有限公司