


THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.

REV.	ECN NO.	DATE	SIGN	DESCRIPTION
A		2020/02/03	Vicky	Initial Released




AB-CBD XX FL-CBDFL-QF XXX

08: 8Pin

XXX: 0.5~99Meters
 A05: 0.5 Meter
 001: 01 Meter
 002: 02 Meters
 :
 099: 99 Meters

Note:

- * ⊘ Important Dimension
- * Waterproof Rate: IP68, Mated
IP68: 1M depth of water in 24hours
- * Connector: Thermoplastic, Black
- * Pin: Copper Alloy, Gold Plated
- * Cable: UL21996, 16#*3C+(26#*2P+D+AL/MY)+AL/MY, PVC Jacket, Black, OD11.0mm
- * Cable Length Tolerance: 0.5M: +60/-0mm
 01M: +60/-0mm
 02~03M: +120/-0mm
 04~05M: +160/-0mm
 06~10M: ±100mm
 11~20M: ±200mm
 21~30M: ±300mm
 31~99M: ±500mm



C1 & C2
Pin Assignments
Front View

8	Drain (26AWG)	地線	Twist 對線
7	Blue (26AWG)	藍	
6	Red (26AWG)	紅	Twist 對線
5	Green (26AWG)	綠	
4	White (26AWG)	白	
3	Black (16AWG)	黑	
2	Green (16AWG)	綠	
1	White (16AWG)	白	
C1 & C2	Wire Color		
Pin Out			

UNIT:mm	⊘	TITLE
TOLERANCE	⊘	ACC, XLOK, C-10A+5A, DB-ENDED FF
±0.5mm		
SCALE	SIZE	SHEET
33:100	A4	1 OF 1
REV.	WC-REV.	⊘ : Inspection item
A	A.5	

Amphenol LTW
 安費諾亮泰企業股份有限公司

ITEM NO	DRAWN BY	DATE
	Vicky	2020-02-03
DWG NO	CHECKED BY	DATE
AB-CBDXXXFL-CBDFL-QFXXX	Rita	2020-02-03
CUSTOMER	APPROVED BY	DATE
ALTW	Max	2020-02-03