



THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.

REV.	ECN NO.	DATE	SIGN	DESCRIPTION
A		2020/01/21	Ruru	Initial Released



Note:

- \*  $\text{Ⓞ}$  Important Dimension.
- \* Waterproof Rate: IP68, Mated.  
IP68: 1M depth of water in 24 hours.
- \* Connector: Thermoplastic, Black.
- \* Pin: Copper Alloy, Gold Plated.
- \* Cable: UL21996, (26#\*4P+D+AL)+12#\*3C+AL, PVC Jacket, Black, OD13.5
- \* Cable Length Tolerance: 0.5M: +60/-0mm  
01M: +60/-0mm  
02~03M: +120/-0mm  
04~05M: +160/-0mm  
06~10M: ±100mm  
11~20M: ±200mm  
21~30M: ±300mm  
31~99M: ±500mm

UNIT:mm		TITLE	ACC, XLOK, D-20A+5A, DB-ENDED MF
TOLERANCE	±0.5 mm	SCALE	1:2
		SIZE	A4
		SHEET	1 OF 2
		REV.	A
		WC-REV.	
		$\text{Ⓞ}$	Inspection item


**Amphenol LTW**  
安費諾亮泰企業股份有限公司

ITEM NO	DRAWN BY	DATE
	Ruru	2020-01-21
DWG NO	CHECKED BY	DATE
AB-DCDXXHL-DCDBR-QFXXX	Rita	2020-01-21
CUSTOMER	APPROVED BY	DATE
ALTW	Max	2020-01-21


AB- DCD XX H L - DCD B R - Q F XXX

12: 12Pin

XXX: 0.5~99Meters  
 A05: 0.5 Meter  
 001: 01 Meter  
 002: 02 Meters  
 :  
 099: 99 Meters



C1  
Pin Assignments  
Front View



C2  
Pin Assignments  
Front View

12	Drain (26AWG)	地線
11	Gray (26AWG)	灰
10	Yellow (26AWG)	黃
9	Orange (26AWG)	橘
8	Violet (26AWG)	紫
7	Blue (26AWG)	藍
6	Red (26AWG)	紅
5	Green (26AWG)	綠
4	White (26AWG)	白
3	Black (12AWG)	黑
2	White (12AWG)	白
1	Green (12AWG)	綠
Conn.	Wire Color	
	Pin Out	

Twist  
對線

Twist  
對線

Twist  
對線

Twist  
對線

UNIT:mm

TOLERANCE  
± 0.5 mm

TITLE ACC, XLOK, D-20A+5A, DB-ENDED MF

SCALE 1:2	SIZE A4	SHEET 2 OF 2
REV. A	WC-REV.	QC: Inspection item

**Amphenol LTW**  
安費諾亮泰企業股份有限公司

ITEM NO	DRAWN BY Ruru	DATE 2020-01-21
DWG NO AB-DCDXXHL-DCDBR-QFXXX	CHECKED BY Rita	DATE 2020-01-21
CUSTOMER ALTW	APPROVED BY Max	DATE 2020-01-21