


THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.

5	6	7	8
REV.	ECN NO.	DATE	SIGN




BB-03BFMM-SR6000 (1)
Color: Black




BB-03BFMM-SR6AXX

- XX:01~99Meter
- 01:01Meter
- 02:02Meters
- ⋮
- 99:99Meters

Cable Length(L):01~99Meters



Conn.



Pin Assignments
Front View

3	Yellow
2	White
1	Black
Conn.	Wire Color
Pin Out	

Note:

- * @D Important Dimension To Check.
- * Waterproof Rate: IP66
- * Housing: Black, Nylon+GF
- * Pin: Copper Alloy, Gold Plated
- * Cable: Black, UL2464 20AWG*3C+Al/My
PVC Jacket UV Resistant, OD=5.0mm
- * Cable Length Tolerance: 1M~10M±5%mm, 11M~99M±500mm.

UNIT:mm	
TOLERANCE	±0.5 mm

TITLE Standard	
Cable Screw 3Pin F Conn. M Pin	
SCALE Free	SHEET 1 OF 1
REV. A	SIZE A4
@C : Inspection Item	

Amphenol LTW
安費諾亮泰企業股份有限公司

ITEM NO	
DWG NO	BB-03BFMM-SR6AXX
CUSTOMER	ALTW

DRAWN BY	Allan Frank Valentino
CHECKED BY	Robert Dabu
APPROVED BY	Win

DATE	2007/02/06
DATE	2007/02/12
DATE	2007/02/12