


5	6	7	8
REV.	ECN NO.	DATE	SIGN

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.




BD-05BFMM-SR6000 ①
Color: Black




BD-05BFMM-SR6AXX

- XX:01~99Meter
- 01:01Meter
- 02:02Meters
- ⋮
- 99:99Meters

Cable Length(L):01~99Meters



Conn.



Pin Assignments
Front View

5	Green
4	White
3	Black
2	Blue
1	Brown
Conn.	Wire Color
Pin Out	

Note:

- * @C Important Dimension To Check.
- * Waterproof Rate: IP66
- * Housing: Black, Nylon+GF
- * Pin: Copper Alloy, Gold Plated
- * Cable: Black, UL2464 24AWG*5C+D +Al/My, (UV Resistant) OD=5.0
- * Cable Length Tolerance: 1M~10M±5%mm, 11M~99M±500mm.

UNIT:mm	TITLE Standard Cable Screw 5Pin F Conn M Pin		Amphenol LTW 安費諾亮泰企業股份有限公司	ITEM NO	DRAWN BY Raul Paulo Canja	DATE 2007/02/10
TOLERANCE ±0.5 mm	SCALE Free	SHEET 1 OF 1		DWG NO BD-05BFMM-SR6AXX	CHECKED BY Robert Dabu	DATE 2007/02/12
REV. A	SIZE A4	@C :Inspection Item	CUSTOMER ALTW	APPROVED BY Win	DATE 2007/02/12	8 FMWIO702-01-01A2