


REV.	ECN NO.	DATE	SIGN	DESCRIPTION
B	LEN-790211	2007/09/13	WUFEI	Change Nut
C	LEN-920168~71	2008/09/29	Li Xiu Zhi	Change Front View
D	LEN1710144~47	2017/01/17	Ruru	Change Logo




BSD-08BFFM-SR6000
Color: Black



BSD-08BFFM-SR6AXX

XX:01~99Meter
01:01Meter
02:02Meters
:
:
99:99Meters

Cable Length(L):01~99Meters



Conn.



Pin Assignments
Front View

Shield	Drain	地線
8	Green	綠
7	Yellow	黃
6	Orange	桔
5	Red	紅
4	Blue	藍
3	White	白
2	Brown	棕
1	Black	黑
Conn.	Wire Color	
	Pin Out	

Note:

- * @@ Important Dimension To Check.
- * Waterproof Rate: IP66
- * Housing: Black, Nylon+GF
- * Pin: Copper Alloy, Gold Plated
- * Cable: Black, UL2464 24AWG*8C+Drain+Al/My (UV Resistant), OD=5.5
- * Cable Length Tolerance: 01M:40mm
02M~05M:60mm
06M~10M:100mm
11M~30M:200mm
31M~99M:500mm

UNIT:mm	
TOLERANCE	±0.5 mm

TITLE Standard, Cable Screw 8Pin F Conn F Pin	
SCALE Free	SHEET 1 OF 1
REV. D	SIZE A4
QC : Inspection Item	

Amphenol LTW
安費諾亮泰企業股份有限公司

ITEM NO	DWG NO	CUSTOMER
	BSD-08BFFM-SR6AXX	ALTW

DRAWN BY	CHECKED BY	APPROVED BY
Ruru	Rita	Max

DATE	DATE	DATE
2017/01/17	2017/01/17	2017/01/17

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.

1 2 3 4 5 6 7 8

F

E

D

C

B

A

1 2 3 4 5 6 7 8

FMMI0702-01-01A2