



REV.	ECN NO.	DATE	SIGN	DESCRIPTION
C	C201441	2020/09/17	Vicky	△ X2
D	C210219	2021/03/15	Vicky	△ X4
E	C210796	2021/05/24	Vicky	△ X1



Pin Out	Wire	Color	Color
5	Green	綠	綠
4	Black	黑	黑
3	Blue	藍	藍
2	White	白	白
1	Brown	棕	棕



△ 12P-XXBMIM-SR8BXX
 XX: No. Of Pin
 XX: 01~99Meters
 01: 01Meter
 02: 02Meters
 :
 :
 99: 99Meters
 Cable Length(L): 01~99Meters

- △ Note:
- * RoHS Compliant
 - * @C Important dimension
 - * Waterproof rate: IPX8, mated 1m/24h
 - * Connector
 - △ Housing: Thermoplastic, Black
 - Pin: Copper alloy, Gold plated
 - Nut: Thermoplastic, Black
 - Outer mold: Thermoplastic, Black
 - * Cable: 22#*5C+Insulation, OD=5.0mm, PU Jacket, Black
 - △ * Cable length tolerance:
- | | |
|------------------|------------|
| 1M: | +50/-0 mm |
| 1M < L ≤ 3M: | +100/-0 mm |
| 3M < L ≤ 5M: | +150/-0 mm |
| 5M < L ≤ 10M: | ±100 mm |
| 10M < L ≤ 20M: | ±200 mm |
| 20M < L ≤ 30M: | ±300 mm |
| △ 30M < L ≤ 99M: | ±500 mm |

Pin Assignments Front View

UNIT:mm		TITLE
TOLERANCE	±0.5mm	O SEN, M12 A -PLASTIC(I) △ △ CABLE W/O SR, M, I, MOLDING
SCALE	Free	SHEET 1 OF 1
REV.	E	SIZE A4
		@C : Inspection Item

Amphenol LTW
 安費諾亮泰企業股份有限公司

ITEM NO	DRAWN BY	DATE
DWG NO	CHECKED BY	DATE
CUSTOMER	APPROVED BY	DATE

Zhao Rong Fu
 Tina
 Luke
 2009/02/04
 2009/02/04
 2009/03/13

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.